

Straight Blade Devices 15A, 125V, 2 Pole, 3 Wire Grounding Insulgrip Plug

HUBBELL

Features

- Ribbed nylon housing is impact and chemical resistant
- VARI-SIZE adjustable cord clamp
- Fast lead assembly screws
- Beveled housing prevents snagging

Ordering Information

Description	Cord Diameter	UPC	Catalog Number
Black nylon with extra large cord clamp	.360"-.720"(9.1-18.3)	783585366111	HBL5266EBK

Listings

UL Listed to UL498 File E1706
CSA Certified to C22.2 No. 42 File 280
Fed. Spec. W-C596G
NEMA® WD-6 Compliant

Specifications

Housing/Cord Clamp	Nylon
Blade Holder	Nylon
Terminal Retainer	Clear Polycarbonate
Blades	.060 in. (1.5) Brass
Terminal Screws	#8-32 Brass , multiple drive
Terminal Clamp	Nickel plated steel
Assembly Screws	Nickel plated steel

Performance

Electrical

Current Interrupting	Certified for current interrupting at full rated current
Dielectric Voltage	Withstands 2,000V minimum

Mechanical


Cord Accomodation	.360"-.720"(9.1-18.3)
Terminal Accommodation	#18-10 AWG. Standed copper wire only
Terminal Identification	Terminals identified in accordance with UL 498 and CSA

Environmental

Flammability	UL 94 HB or better
IP Suitability	IP20
Operating Temperatures	Maximum continuous 75°C; minimum -40°C (w/o impact)




AGENCY LISTING
PER TABLE




ALL SCREWS ARE
COMBINATION
ROBERTSON/PHILLIPS/
SLOTTED HEAD

1.968 ± 0.031
[49.99 ± 0.79mm]



INTEGRAL VARI-SIZE®
INSERT



CATALOG NUMBER
(HBL5266CM2 &
HBL5266EBK NOT
MARKED)

∅ 1.527 ± 0.015
[38.74 ± 0.38mm]

Accessories

Weatherproof Boot	HBL6017
-------------------	---------

Resources

eCatalog	
----------	--

Distributor:



Phone: 407-857-8770

Fax: 407-857-8771

Email: sales@techni-lux.com

www.techni-lux.com

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

