



# NAC3PX

# power CON TRUE1

Appliance inlet-outlet combination, 1/4" flat tab terminals

The powerCON TRUE1 is a locking 20 A true mains connector. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection.

The powerCON TRUE1 is a connector with breaking capacity (CBC), i.e. it can be connected or disconnected under load or live.



## Features & Benefits



Appliance inlet-outlet combination for daisy-chaining

- True mains connector with breaking capacity (CBC)
- Lockable 20 A single phase connector
- Easy and reliable twist lock system
- Extremely robust and reliable
- ENEC certified according to IEC 60320
- UL recognized components
- IP65 – water resistant when mated with ready-made cord sets

## Technical Information

Product	
Title	NAC3PX
Electrical	
Contact resistance	≤ 3 mΩ (inner)
Dielectric strength	4 kVdc / 2.8 kVac
Insulation resistance	> 0.1 GΩ (after damp heat test IEC 68-2-30)
Number of electrical contacts	2 + PE
Rated current per contact	16 A rms (USA: 20 A)
Rated voltage	250 V ac
Mechanical	
Lifetime	> 5000 mating cycles
Wiresize	2.5 mm <sup>2</sup>
Wiresize	12 AWG
Environmental	
Flammability	UL 94 V-0
Temperature range	-30 °C - +80 °C
Accessories	

### SCNAC-PX

The rubber sealing cover protects the powerCON TRUE1 duplex chassis connector NAC3PX from dust and water according to protection class IP65.



## APPLIANCE COMBINATION



Mating scenario powerCON TRUE1 chassis connector NAC3PX

**Distributor:**

  
**Techni-Lux**  
 www.techni-lux.com

Phone: 407-857-8770  
 Fax: 407-857-8771  
 Email: sales@techni-lux.com