



Head Quarter: **STUDIO DUE** s.r.l.
Str. Poggino, 100 - 01100 Viterbo (Italy)
tel. +39.0761.352520 (4 lines)
fax +39.0761.352653

STUDIO DUE UK
3 Encon Court, Owl Close
Moulton Park Industrial Estate
Northampton (England) UK - NN3 6 HZ
tel. +44.1933.650.820

STUDIO DUE Far East LTD
Flat B 12/F - Shun Wai Industrial Building
15 Yuk Yat Street - Tokwawan Kowloon (Hong Kong)
tel. +852.29542141 fax +852.23302515

STUDIO DUE Lighting Technology (Shen Zhen) LTD

www.studiodue.com

emotion and creativity in light

Studio Due

rel.1_08/08

graphics: vilfredo maria ricci - print: Ambrosini - © 2008 studio due

Archi¹⁵⁰bar



Studio Due



Archibar 150 is a Studio Due powerful IP 67 wash led light fixture! Dashing and compact, Archibar 150 is made in aluminium and is equipped with 16 group (rgbw) each one with 4 units of 3W Luxeon Rebel led's. The optics, realized in special material, allow brilliant light and a very homogeneous beam. Standard optics are 25°. On request is possible to install the optional wide optics 40°.



Inside, the microswitches provide to set-up the fixture.



ARCHIBAR 150/C specifications

SOURCE (LED Luxeon Rebel)
16 group (RGBW) with four units of 3W Led's

OPTIC
25mm lenses standard beam (25°)
On request:
wide beam lenses kit (40°)

TILT
Tilt: 120°

CONTROL
Standard interface: RS-485; opto-couplet input.
Protocol: USITT DMX 512 - 9 channels

SETUP AND CONFIGURATION
Inside with microswitches
Internal preset with master/slave function

IP RATE
IP 67 fixture, main power and DMX cable connections

POWER SUPPLY
Switching power supply (universal main voltage)
Rated voltage: 100-240V~; 50-60Hz
Rated power: 180W
Rated current: 1A @ 230V

DMX CHANNELS
ch1 = red
ch2 = green
ch3 = blue
ch4 = white
ch5 = strobe
ch6 = dimmer
ch7 = led fade time
ch8 = rainbow
ch9 = white balanced

PHYSICAL
Width: 1005 mm
Height: 255 mm (max)
Weight: 7 kg.



Archibar 150 is equipped with floor bracket for easy installations.



available version:
art. 0806: rgbw ARCHIBAR 150/C

available accessories:
art. AB-40BL: 40° wide beam lenses kit

For permanent installations is possible to remove the floor bracket and fix the unit on a surface. Anyway you have 120° tilt regulation.