

**P-5 Wash Light**

Specifications	Optics	Light source LEDs expected lifetime Interchangable lens option	44 x High power 10W RGBW LEDs 50,000 hours* 15°, 21° & 43°
	Photometric	Light output Efficacy	23,500 lumen (43° lens) 58 lm/W
	Features	Pan/Tilt	+ / - 90°
	Electrical	AC Power Maximum power consumption Typical power consumption Power factor	208 - 240 V Nominal 50/60 Hz 450 W (all LEDs on) 420 W (all LEDs on) 0.98 PF (230 V)
	Programming and Control	Protocol Setting and addressing  DMX channels	USITT DMX512 A Wireless DMX (LumenRadio) RDM Stand alone mode (programmable by RFID) Oled graphical display / 4 buttons Software upgradeable via Uploader cable (P/N:83062011) 3, 4, 6, 8, 9 or 10
	Physical	Dimensions (L x H x W) Weight Material Lens IP class	497 x 268 x 122 mm (19.6 x 10.6 x 4.8 in) 8.9 kg (19.6 lbs.) Aluminium PE and tempered glas front IP65
	Installation	Mounting Rigging possibilities Safety features	Any, but facing 100% down for permanent installation Floor stand (included) or hanging (Omega Clamps included) Bottom mount for Safety wire
	Thermal	Temperature range, Operating Temperature range, Start-up Humidity (max.) Cooling	-10° – 40°C (-14° – 104°F) -10° – 40°C (-14° – 104°F) 98% Active, Forced air, temperature-regulated, low noise
	Connections	DMX data in/out	IP65 Neutrik HD locking XLR 5-pin cable 0.5m, for DMX in and out Power cable 0.5m with bare ends
	Certified to Conforms to	CSA Std. C22.2 No. 166 UL Std. 1573 2006/95/EC: Low Voltage Directive 2004/108/EC: EMC Directive RoHS2 Directive	EN 60598-1, EN 60598-2-17, EN 62471 EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3 2011/65/EU
	Included Items	Included Items	Floor Stand (incl. screws) 2 pcs Omega brackets Wireless DMX G4 antenna User manual Neopren pouch
	Fixtures and Accessories	Fixtures  Lens/s  Brackets  Floorstand Barndoor  Cables Flight case	Order no: 80030517 - P-5 Wash Light (43°) Order no: 80030515 - P-5 Wash Light (21°) Order no: 80030518 - P-5 Wash Light (15°)  Order no: 83061104 - P-5, Lens kit (43°) Order no: 83061103 - P-5, Lens kit (21°) Order no: 83061102 - P-5, Lens kit (15°)  Order no: 83060603 - BCC-2 Dual bracket Order no: 83060604 - BCC-4 Quad bracket Order no: 83060602 - Omega bracket  Order no: 83060610 - Floorstand for P, Q and X series with 1/4-turn fasteners Order no: 83061119 - Accessory Holder P Series Order no: 83061120 - Barndoor 4-way Order no: 83061121 - Barndoor 8-way Order no: 83061122 - Color frame  Order no: 83062011 - SGM USB uploader cable Order no: 82051501 - Flight case for 4 pcs of P-5/Q-7/X-5

\*(Figure provided by manufacturer and obtained under manufacturer's test conditions)

**Distributor:**



Phone: 407-857-8770  
Fax: 407-857-8771  
Email: sales@techni-lux.com