

TECHNICAL DATA

TYPICAL APPLICATIONS

- > A versatile, reliable tape for use in photo studios, film processing laboratories, as well as in home dark rooms.
- > Recommended for use as a chart tape
- > Opaque, matte surface - the "photographer's masking tape"
- > Engineered expressly for quality photographic reproduction work cropping and edging negative for contact printing
- > Sealing camera bellow and film holders against light leaks

ADVANTAGES AND BENEFITS

- > An opaque black, matte finish surface insures the light-free masking required for high quality photo reproduction
- > High quick stick and adhesion
- > Easy, consistent unwind
- > High conformability
- > Hand tearable - no need for cutting tools

CONSTRUCTION

Overall Grade/Function: Photographic masking tape

Backing: Impregnated paper

Adhesive: Synthetic rubber

COLOR(S)

 Black matte (BLK)

STANDARD WIDTH(S)

24 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	21 lbs/in width	36.8 N/10mm
Adhesion to Stainless Steel	50 oz/in width	5.47 N/10mm
Thickness	6.1 mils	0.15 mm
Elongation	7 %	7 %
Service Temperature Range	45 F to 100 F	7 C to 38 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.