


Theater Lighting

Hi-Brite FastFit



Watt	A	B	C	D	E	WxH
Hi-Brite 750	65	26	125	19	41	8.5x9.5
Hi-Brite 1200	84	43	140	25	41	11.7x10.2
1200/115	84	43	140	25	41	12x13
1200/230	84	43	140	25	41	16x16
1200/240	84	43	140	25	41	16x16

Dimensions in mm

Features

1. Philips FastFit.
2. Compact Filament.
3. Philips P3 pinch protection.
4. Compact, shock resistant design.

Benefits

1. Lamp replacement in just seconds, exchangeable with HID lamp.
2. High beam intensity.
3. Enables use at higher temperatures in any burning position. Longer lifetime, fewer early failures, consistent performance over time.
4. Easy handling, ideal for moving head systems.

Type	Wattage	Voltage	Cap/ base	Filament shape	Lumen output	Color temperature	CRI	Efficacy source lm/W	Burning position	Average lamp life h	Max. perm. pinch temp. °C	Nom. Lamp current A	Ordering number
Hi-Brite 750 FastFit	780 W	80V	PGJX50	BP	22500 lm	3250 K	100	30	any	300	500	9.5	release Q4 06
Hi-Brite 1200 FastFit	1200 W	80V	PGJX50	BP	36000 lm	3250 K	100	30	any	200	500	15.0	9245 752 28900
1200/115 FastFit	1200 W	115V	PGJX50	BP	33600 lm	3200 K	100	28	any	300	500	10.4	9245 752 34400
1200/230 FastFit	1200 W	230V	PGJX50	BP	29000 lm	3200 K	100	25	any	300	500	5.2	9245 752 44200
1200/240 FastFit	1200 W	240V	PGJX50	BP	29000 lm	3200 K	100	25	any	300	500	5.0	9245 752 45500



Philips pinch protection technology

- **Reliability**, through longer lifetime and fewer early failures.
- **Quality**, through excellent storage characteristics and consistent performance over time.
- **Compactness**, allowing more compact design of fixtures and burning positions.
- **Philips P3 technology**, Max 500° C pinch temperature
- **No pinch protection**, Max 350° C pinch temperature

Dealer stamp

Distributor:



Phone: 407-857-8770
 Fax: 407-857-8771
 Email: sales@techni-lux.com