GE Consumer & Industrial Specialty Lighting

CSR Lamps



The GE CSR6000/DE is a double ended metal halide lamp that provides high efficiency, excellent color rendering, hot restrike capability, and a daylight color temperature. The CSR6000/DE is used in the film and event lighting field of entertainment lighting.

x 0.323

y 0.325

6,000K

MAX450


MAX56

300hr

25x51 Cyl 165mm

22(MAX)mm

Product Description CSR6000/DE	
•Order Description	CSR6000/DE
Product Code	48456
 Pack Quantity 	6
•Rated Wattage	6,000W
Rated Voltage	125± V
•Lamp Current (ECG/MCG)*	48.0A
 Ignition Voltage (cold/hot) 	8/60(MAX)
•Lumens	570,000 Lm
•Lumens per watt	95
•Ra	>90



*ECG = electronic control gear/ MCG = Magnetic control gear

Lamp Operation

Chromaticitu

coordinates

Arc Length

Base

Lamp length

•Color temperature

 Light center length •Lamp diameter

Average rated life

Burn Position H15 350°C Maximum Seal Temperature Cooling Forced Cooling/Fan Lamp can be used on electronic or AC magnetic **Ballast/igniters**



🕼 and General Electric are both registered trademarks of the General Electric Company, USA. 💿 General Electric Company (USA) 2006

umer & Industrial Specialty Lighting is constantly developing and improving its products. For this reason, all product descriptions bchure are intended as a general guide, and we may change specifications tune to time in the interest of product development, into notification or public announcement. All descriptions in this publication present and general particulars of the goods to greater and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. 6. El uphing contract accept any lability arising from the relations ensure that that the terminate primited by two. CSR6000/DE - Data sheet - April 2008

Application Information

- Do not exceed rated wattage or voltage
- Replace lamp at or before rated life
- Do not exceed rated seal temperature
- Use only with properly rated fixtures and ballasts

Distributor:



Phone: 407-857-8770 Fax: 407-857-8771 Email: sales@techni-lux.com