

OVER A DECADE OF GANTOM

Gantom Lighting & Controls, formerly Darklight, was founded in the Spring of 2010 as a manufacturer of special-effects lighting equipment catering to the themed attraction industry. We specialize in illumination of low-light and space-constrained environments where traditional theatrical luminaires aren't suitable. Our award-winning products have become the "secret weapon" of many lighting designers and industry experts and have been installed in a wide range of venues around the world including theme parks, museums,

Gantom is a combination of "Gan," our founder's last name, and "Phantom," which reflects our humble Halloween lighting beginnings.

ILLUMINATE AND INSPIRE!

PRECISION SERIES

LIGHTING FIXTURES

The Precision Series is our all-purpose luminaire range. These tiny yet powerful fixtures have found themselves in a variety of applications such as miniature models, haunted attractions, props, and ride vehicles.



PRECISION SERIES

| PRODUCT NAME | Precision Z Spot Micro Spotlight | Precision Z Flood Micro Floodlight | Precision Alpha Micro Pinspot |
|--|--|---|---|
| PRODUCT HIGHLIGHT | High brightness fixture with far throw and intense color | Wide beam angle fixture for highlights and color mixing | Multi-use spotlight with adjustable color, angle, and brightness (filters included) |
| BEAM / FIELD | 11° / 32° | 62° / 84° | 13° / 28° |
| DIMENSIONS | 42mm x 40mm x 50mm 1.65" x 1.57" x 1.96" | 42mm x 40mm x 50mm 1.65" x 1.57" x 1.96" | 71mm x 34mm x 27mm 2.80" x 1.34" x 1.06" |
| ILLUMINANCE (FC/LUX) 1M (3.3FT), 2M (6.6FT), 3M (9.9FT) | 883 lx (82.0 fc), 221 lx (20.5 fc), 100 lx (9.3 fc) | 66 lx (6.1 fc), 15 lx (1.4 fc), 5lx (0.5 fc) | 843 lx (78.3 fc), 219 lx (20.4 fc), 97 lx (9.0 fc) |
| LED COLOR OPTION(S) | R G B A CW WW UV* *UV for Spotlight Only | | CW WW Adjustable with Gel Filters |
| POWER (12-24VDC) | 1.5W | 1.5W | 1.5W |
| DIMMING | PWM or DMX Available | PWM or DMX Available | PWM |
| IP RATING | IP65 | IP65 | IP65 |
| SUITABLE ENVIRONMENTS | Indoor or temporary outdoor | Indoor or temporary outdoor | Indoor or temporary outdoor |
| FINISH OPTION(S) | Black Anodized Finish | Black Anodized Finish | Black Anodized Finish |
| APPLICATIONS | Immersive environments, museums, display cases | lmmersive environments, museums, display cases | Museums, retail, display cases |
| PRODUCT IMAGE | | | |









GANTOM SERIES

LIGHTING FIXTURES

The Gantom Series is our most popular line of theatrical fixtures designed for a range of themed entertainment applications including live performances, theme parks, museums, and retail. This series offers superior beam and color control in a package that fits in the palm of your hand.



GANTOM SERIES

| PRODUCT NAME | Gantom DMX V2 Color Mixing DMX Spotlight | Gantom R4 Recessed DMX Spotlight | Gantom 7 Seven-Color DMX Spotlight |
|--|--|--|---|
| PRODUCT HIGHLIGHT | Compact DMX controlled spotlight with smooth dimming and excellent color control | Compact recessed fixture with adjustable optics, smooth dimming, and excellent color control | Versatile fixture with full color and beam control designed to handle all theatrical lighting needs |
| BEAM / FIELD | 16° / 32° (Diffusible with included filters) | 16° / 32° (Diffusible with included filters) | 15° / 35° (Diffusible with included filters) |
| DIMENSIONS | 58mm x 49mm x 63mm 2.28" x 1.93" x 2.48" | 70mm x 55mm x 40mm 2.76" x 2.17" x 1.57" | 92mm x 69mm x 70mm 3.62" x 2.72" x 2.76" |
| ILLUMINANCE (FC/LUX) 1M (3.3FT), 2M (6.6FT), 3M (9.9FT) | 883 lx (82.0 fc), 221 lx (20.5 fc), 100 lx (9.3 fc) | 883 lx (82.0 fc), 221 lx (20.5 fc), 100 lx (9.3 fc) | 650 lx (60.4 fc), 220 lx (20.5 fc), 100 lx (9.3 fc) |
| LED COLOR OPTION(S) | RGBW (6500K) or DW (2650K - 6000K) | RGBW (6500K) or DW (2650K - 6000K) | R, G, B, A, W (6500K), Lime, UV (395nm) |
| POWER (12-24VDC) | 4.8W | 4.8W | 7.5W |
| DIMMING | DMX | DMX | DMX |
| IP RATING | IP65 | IP60 | IP65 |
| SUITABLE ENVIRONMENTS | Indoor or temporary outdoor | Indoor only | Indoor or temporary outdoor |
| FINISH OPTION(S) | Black Anodized Finish | Black Anodized Finish | Black Anodized Finish |
| APPLICATIONS | Themed entertainment, theater, museums, film & television | Hospitality, architainment, themed entertainment, display cases | Theater, themed entertainment, live events |
| PRODUCT IMAGE | | Sent Sent Sent Sent Sent Sent Sent Sent | |




HIGH QUALITY LED LIGHTING

NEW CRI STANDARDS FOR GANTOM LUMINAIRES

Never sacrifice on color quality when using LED lights. Gantom fixtures are now 90+ CRI for all color temperatures 3000K or lower. Photometric data and TM-30 reports are available on our website.

To learn more about upgrades to our lighting lineup, schedule a Virtual Gantom Product Demonstration with one of our Application Specialists at www.gantom.com/demo





| PRODUCT NAME | Gantom One / One DMX Compact Pinspot | Gantom iQ / iQx Gobo Projector with Zoom Lens | Gantom Juni / Juni DMX Framing Projector with Zoom Lens |
|--|--|---|---|
| PRODUCT HIGHLIGHT | LED pinspot with ultra narrow beam optics, diffusion lenses and magnetic retaining ring included | Micro LED gobo projector with integrated DMX controlled effects | The smallest framing projector in the world with sharp optics and precise focus adjustments |
| BEAM / FIELD | 2.7° / 4.5° (Diffusible with included filters) | 25° - 40° (Adjustable zoom lens) | 25° - 38°, 40° - 60° (Adjustable zoom lens) |
| DIMENSIONS | 79mm x 69mm x 70mm 3.11" x 2.72" x 2.76" | 94mm x 49mm x 50mm 3.7" x 1.93" x 1.97" | 129mm x 89mm x 79mm 5.08" x 3.50" x 3.11" |
| ILLUMINANCE (FC/LUX) 1M (3.3FT), 2M (6.6FT), 3M (9.9FT) | 22,100 lx (2053.2 fc), 8,100 lx (752.5 fc), 4,100 lx (380.9 fc) | 510 lx (47.4 fc), 123 lx (11.4 fc), 53 lx (4.9 fc) | 1,620 lx (151 fc), 405 lx (38 fc), 180 lx (17 fc) |
| LED COLOR OPTION(S) | CW WW Adjustable with Gel Filters | CW WW Adjustable with Gel Filters | CW WW Adjustable with Gel Filters |
| POWER (12-24VDC) | 4.8W | 2.8W | 9W* 12VDC ONLY WITH NON-DMX JUNI |
| DIMMING | PWM or DMX Available | PWM or DMX Available | Low-Voltage Dimming or DMX Available |
| IP RATING | IP65 | IP40 (IP65 with FA30) | IP50 |
| SUITABLE ENVIRONMENTS | Indoor or temporary outdoor | Indoor or temporary outdoor (with FA30) | Indoor only |
| FINISH OPTION(S) | Black Anodized Finish | Black Anodized Finish | Black Anodized Finish |
| APPLICATIONS | Centerpiece illumination, hospitality, the- ater, museums. | Retail, theater, special effects, logo projection | Retail, themed entertainment, theater, hospitality, museums |
| PRODUCT IMAGE | | | |



POWER SUPPLIES

| PRODUCT NAME | PowerPak MIni 12V/1A Power Supply | PowerPak 5000 12V/5A Power Supply | PowerPak Pro 12V/5A Outdoor Power Supply | PowerPak Max 24V/8A Indoor/Outdoor Power Supply | PowerPak Plug-and-Play 24V/8A Power Supply with Trunk Cable |
|----------------------|--|--|--|--|--|
| PRODUCT HIGHLIGHT | The PowerPak Mini is a small, UL listed AC adapter suitable for any of our LED luminaires and is ready to plug into your wall outlet. Unit comes with a screw terminal adapter to allow for easy splicing. | The PowerPak 5000 is a UL listed 60W power supply that comes with a DC to screw terminal adapter to allow for easy wire splicing to multiple fixtures. | The PowerPak Pro is a regulated power supply with bare wire leads and an aluminum housing suitable for permanent installations and outdoor applications. | The PowerPak Max provides the maximum recommended power for a Gantom system. Operating at 24VDC instead of 12VDC helps reduce the voltage drop in the wires, allowing you to extend your cable runs further. | The PowerPak Plug and Play is the perfect way to inject power and DMX into your Gantom Pro Cable system with an Edison plug for easily connecting to a wall outle tand a male 5pin XLR connector for inputting a DMX control signal. On the output side is a single female Gantom Pro Cable Trunk connector. |
| INPUT | 100-240 VAC 50/60Hz | 100-240VAC 50/60Hz | 100-265VAC 47~63Hz | 100-305VAC 47~63Hz | 100-277VAC 47/63Hz |
| OUTPUT | 12VDC | 12VDC | 12VDC | 24VDC | 24VDC |
| POWER RATING | 1A maximum load (12W) | 5A maximum load (60W) | 5A maximum load (60W) | 8.33A maximum load (200W) | 8.33A maximum load (200W) |
| IP RATING | IP60 | IP60 | IP67 | IP67 | _ |
| PRODUCT IMAGE | | | | | |

PRO CABLE DISTRIBUTION

| PRODUCT NAME | GP002 G8 Distribution Box | GP003 G8 Distribution Box | GP004 G8 Distribution Box | CB124 T Connector |
|--------------------------|--|--|---|---|
| DESCRIPTION | Indoor/Outdoor Field Install Power and DMX Distribution Box | Indoor Plug-and-Play Power and DMX Distribution Box | Plug-and-Play Power and DMX Distribution Box | Pro Cable System T Connector with Integrated DMX Repeater |
| PRODUCT HIGHLIGHT | Designed to fit your application, this G8 Distribution Box allows you to tailor your Gantom Pro Cable system to you needs | Quick and easy to set up, the Plug-and-Play G8 makes Pro Cable quick and secure to use | The power of the G8 Distribution Box with the versatility of Trunk Cable - Compatible with T Connectors and related accessories | Individual fixture power and data distribution with Trunk Cable connections allow for flexible system layouts |
| DIMENSIONS | 204mm x 200mm x 92mm 8.03" x 7.87" x 3.62" | 200mm x 94mm x 65mm 7.87" x 3.70" x 2.56 | 200mm x 94mm x 65mm 7.87" x 3.70" x 2.56 | 119mm x 64mm x 24mm 4.67" x 2.50" x 0.94" |
| POWER INPUT | 12-24VDC, 5A maximum | 12-24VDC, 5A maximum | 12-24VDC, 7A maximum | 12-24VDC, 7A maximum |
| # OF SUPPORTED FIXTURES | 8 units (one per port) | 8 units (one per port) | 8 units (one per port) | 1 unit |
| IP RATING | IP67 | IP40 | IP60; IP65 with CB147 Caps | IP65 |
| SUITABLE ENVIRONMENTS | Permanent outdoor or indoor installation | Permanent indoor; Temporary indoor or outdoor installation | Permanent indoor or outdoor installation | Permanent indoor or outdoor installation |
| MATERIAL | ABS Plastic Housing | ABS Plastic Housing | ABS Plastic Housing | Durable Molded PVC Material |
| COMPATIBLE COMPONENTS | Branch Cables: CB141, CB138, CB132, CB133, CB134 Power Supplies: PP33, PP35 | Branch Cables: CB139, CB130, CB131 Power Supplies: PP31, PP33, PP35 | Trunk Cables: CB129, CB120, CB121, CB122, CB137 Branch Cables: CB139, CB130, CB131 Power Supplies: PP33, PP35, PP36 | Trunk Cables: CB129, CB120, CB121, CB122, CB137 Branch Cables: CB139, CB130, CB131 Power Supplies: PP33, PP35, PP36 |
| | | | | |

PRODUCT IMAGE













FIXTURE ACCESSORIES

| PRODUCT NAME | Gantom DarkBox Programmer V2 Standalone Programming Device for Gantom Light Fixtures | GoCable Power Indoor Power Cable | Ping Trim Kit Recessed Trim for Gantom Fixtures | Ping G Series Glasstop Display Mount |
|------------------------|---|--|---|--|
| PRODUCT HIGHLIGHT | The DarkBox Programmer offers a simple and reliable way to configure the settings of Gantom light fixtures. Now all of the functionality of our Gantom Programmer app is available in a standalone device. | Gantom GoCable makes wiring Gantom fixtures fast and easy. Various lengths of extensions and splitters make placing any connection exactly where you need it a simple task. | This recessed trim mount allows you to install a Gantom fixture in a ceiling for downlighting. The swivel adjustment allows you to precisely aim the fixture with a total of 40° of adjustment. | Designed to allow Gantom fixtures to sit comfortably and discreetly atop glass display cases. |
| FINISH OPTION(S) | High-visibility yellow silicon cover | Black | Black or silver anodized finish | Black anodized finish |
| COMPATIBLE PRODUCTS | All DMX controllable Gantom fixtures | All non-DMX controllable Gantom fixtures | Trim Kits available for Precision Z Spot and Flood, Gantom DMX V2, Gantom One (DMX), Gantom iQ(x), and Gantom 7 | Precision Z Spot and Flood |
| PRODUCT IMAGE | | | | |

FIXTURE ACCESSORIES

| PRODUCT NAME | Recessed Canopy Mount Mounting Accessory for Gantom Fixtures | Glare Control Accessories Accessories for beam control and glare prevention | Ground Stakes 160mm and 205mm Ground Stakes |
|------------------------|---|---|---|
| PRODUCT HIGHLIGHT | This mount allows for clean surface installation of any Gantom light fixture. The mount allows for neat cable entry into the space above. | Gantom's beam control accessories shield the light source from view, causing the fixtures to fade further into the background. Secure a gel filter or diffuser to the fixture using the included internal ring. | Ground stake accessories for mounting Storm Series fixtures are available for all sizes of fixture. We recommend using FA40 for the Storm Z fixtures, and FA41 for all other fixtures. Each ground stake includes hardware for mounting the Storm Series fixture to it. |
| FINISH OPTION(S) | Black anodized finish | Black anodized finish | Black powdercoat finish |
| COMPATIBLE PRODUCTS | All Gantom series fixtures | Accessories available for Precision Z Spot and Flood, Gantom DMX V2, Gantom One (DMX), Gantom iQ(x), Juni (DMX), and Gantom 7 | All fixtures |
| | | | |

PRODUCT IMAGE







SPECIALTY OFFERINGS

Gantom offers unique solutions for all of your project needs. These offerings are custom manufactured for your application. We want to work with you to help you find the right solution for your lighting designs!

GANTOM ON TRACK

Gantom now offers our fixtures pre-assembled to track adapters for Eutrac's LED-Trac low voltage track system. This system is UL listed, low voltage, compact, and offers full DMX control and addressing of individual fixtures. Track dramatically simplifies distribution of power and control signal to the lights and allows for clean and easy installation of many fixtures.



OUTDOOR RATED PRODUCTS FOR PERMANENT INSTALLATIONS

Take on the elements of Mother Nature with solutions for damp and wet location installs. Accessory parts for standard products and full fixture solutions from our Storm series are available to secure Gantom lights in damp or wet locations.



CUSTOM PRODUCTS

Need something else?

Send your lighting needs to **quotes@gantom.com** and we will work with you to try and develop a product that fits your needs!



CONTACT US

MAIN PHONE | 661-347-0779

CALIFORNIA OFFICE

25060 Avenue Stanford, Suite 115 Valencia, CA 91355

FLORIDA OFFICE

7091 Grand National Drive, Suite 103 Orlando, FL 32819

SALES INQUIRIES | SALES@GANTOM.COM

STOCK AVAILABILITY | SALES@GANTOM.COM

PURCHASE ORDERS | ORDERS@GANTOM.COM

QUOTES/PRICING | QUOTES@GANTOM.COM

TECHNICAL SUPPORT | SUPPORT@GANTOM.COM

ACCOUNTING | ACCOUNTING@GANTOM.COM



www.gantom.com | sales@gantom.com 25060 Avenue Stanford, Suite 115, Valencia, CA 91355 Ph. (661) 347-0779